



ABT 30 /60/100 S

Description:

- 1.New 2 beams active infrared detector
- 2.Used for wall,passage etc.
- 3.Anti-glare up to 50,000 LUX, built-in automatic adjustment strong light filtering system
- 4.Up and down optical lens can adjust the mechanical design,making adjustments more faster,convenient and accurate.
- 5.Fully sealed design,rain-proof(fog),dust-proof(worm)
- 6.With high levels of anti-RFI/EMI capability
- 7.Professional anti-jamming optical housing
- 8.Case Material: PC

Parameter:

Model	ABT-30S	ABT-60S	ABT-100S	ABT-150S
Outdoor Alert Distance	30m	60m	100m	150m
Indoor Alert Distance	90m	180m	300m	450m
Beam	2			
Induction Speed	50-700ms			
Alarm Output	NC/NO;Contact rating:30V/0.5A			
Gangled Alarm	Yes			
Working Voltage	DC 12-24V;AC 11-18V			
Working Current	< 100mA			
Tamper Output	NC;Contact rating:24V/0.5A			
Horizontal Angle Adjustment	180 °±90°			
Vertical Angle Adjustment	±10°			
Case Material	PC			
Dimensions	171*82*77mm			

ventas@starx.com.ar

www.starx.com.ar

Pepirí 758
(C1437EIP)
Distrito tecnológico
Ciudad de Buenos Aires
Argentina

+5411.5091.6500
Líneas Rotativas